Model	NG.B408BL								NG.B410DL							
Input	220V 50/60Hz 0.35A								220V 50/60Hz 0.44A							
Output	8kV 30mA 31kHz								10kV 30mA 28kHz							
Min loading(D12mm mercury/argon)	4m								4m							
Protection function	Open circuit, over heat								Open circuit, over heat							
Weight(kg)	0.7								0.7							
Packing	20pcs 15kg								20pcs 15kg							
Packing size(mm)	355x230x245								370x234x215							
Diameter tubing(mm)	7	8	9	10	11	12	13	15	7	8	9	10	11	12	13	15
Gas pressure(mmHg)	18	17	15	13	12	11	10	9	18	17	15	13	12	11	10	9
Load length in meter(clear or red neon)	3	3.5	4	4.5	6	7	7.5	9	4	4.5	5	6	7.5	9	10	12
Load length in meter(mercury/argon)	3.5	4	4.5	6	7	8	9	10.5	4.5	5	6	7.5	9	10	12	14

Notes :

1.All listed values are indicative and represent an average. Values can significantly vary due to filling pressure, temperature, high voltage cable length, electrode type and sign material;

2.Deduct 1 foot for each Pair of electrodes from above load length figures;

3.Footage for mercury filled tubes based on operation at 4℃（40℉）or above. Deduct 25% of footage for operation below 4℃(40℉);

4.The loading shall not exceed the max .value and the minimum value listed in the table when using, the minimum loading of products with different diameter can be calculated according to the max. value.

B408BL



NEON POWER SUPPLY
Model: NG-A408BL
Input: 110V 50/60Hz
1.5A
Output: 8kV 30mA
Load: 4 - 8m (12 neon)
Note: Indoor use only

B410DL


178
162
电源线中途开关
In-line switch
NEON POWER SUPPLY
Model: NG-A410DL
Input: 110V 50/60Hz
1.6A
Output: 10kV 30mA
Load: 4-10m (12 neon)
Note: Indoor use only
70
φ6×400
高 度(high)53mm

Model	NG.A408BL								NG.A410DL							
Input	110V 50/60Hz 1.5A								110V 50/60Hz 1.6A							
Output	8kV 30mA 30kHz								10kV 30mA 30kHz							
Min loading(D12mm mercury/argon)	4m								4m							
Protection function	Open circuit, over heat								Open circuit, over heat							
Weight(kg)	0.812								0.8							
Packing	20pcs 18.24kg								20pcs 18kg							
Packing size(mm)	558×235×273								558×235×273							
Diameter tubing(mm)	7	8	9	10	11	12	13	15	7	8	9	10	11	12	13	15
Gas pressure(mmHg)	18	17	15	13	12	11	10	9	18	17	15	13	12	11	10	9
Load length in meter(clear or red neon)	3	3.5	4	4.5	6	7	7.5	9	4	4.5	5	6	7.5	9	10	12
Load length in meter(mercury/argon)	3.5	4	4.5	6	7	8	9	10.5	4.5	5	6	7.5	9	10	12	14

A408BL


175
160
电源线中途开关
In-line switch
NEON POWER SUPPLY
Model: NG.A408BL
Input: 110V 50/60Hz
1.5A
Output: 8kV30mA
Load:4-8m(Φ12 neon)
Note: Indoor use onl
59
Φ6×400
高 度(high)56mm

NEON POWER SUPPLY
Model: NG.A408BL
Input: 110V 50/60Hz
1.5A
Output: 8kV 30mA
Load:4 - 8m(Φ12 neon)
Note: Indoor use only

A410DL


178
162
电源线中途开关
In-line switch
NEON POWER SUPPLY
Model: NG A4110DL
Input: 110V 50/60Hz
1.6A
Output: 10kV 30mA
Load: 4-10m (ø12 neon)
Note: Indoor use onl
70
ϕ6×400
高 度(high)53mm

NEON POWER SUPPLY
Model: NG A4110DL
Input: 110V 50/60Hz
1.6A
Output: 10kV 30mA
Load: 4-10m (ø12 neon)
Note: Indoor use only